

CyBox LTE 2-W

RAILWAY ROUTER WITH LTE CAT-7 AND WI-FI 5

WESTERMO

DESCRIPTION

SYSTEM ARCHITECTURE	Dual-Core CPU T1023, 1200 MHz 1 GB RAM, 128 MB Flash
POWER SUPPLY	24 to 110 VDC, wide-range power supply (compliant to EN 50155)
AMBIENT TEMPERATURE	depending on temperature class of Wi-Fi module Class OT4, -40.. +70 °C (85 °C) operating or Class OT3, -25.. +70 °C (85 °C) operating -40.. +85 °C storage
STANDARDS	EN 50155

STANDARD CONFIGURATIONS

ORDER NO.	MODEL	LAN 1 (M12 X-CODED)	LAN 2 (M12 X-CODED)	LTE CAT-7	WI-FI 802.11AC 3X3 MIMO	INPUT PSU 24 - 110 VDC (M12 A-CODED)	INPUT POE+ ON LAN 1	USB 2.0 / RS232 (M12 8-PIN A-CODED)	GNSS	ANTENNA CONNECTORS	IP CLASS
3201-0000	CYLTE-1050V0	1 Gbit	1 Gbit	●	●	●	●	●	●	6x QLS	IP40
3201-0020	CYLTE-1052V0	1 Gbit	1 Gbit	●●	-	●	●	●	●	5x QLS	IP40
3201-0030	CYLTE-1055V0	1 Gbit	1 Gbit	●	-	●	●	●	●	3x SMA	IP40

Further information on www.eltec.com and www.westermo.com

Westermo Network Technologies AB
Metallverksgatan 6
72130 Västerås
Sweden

Phone +46 16 42 80 00
Fax +46 16 42 80 01
Email info@westermo.com
www westermo.com | eltec.com

Copyright © 2021 by Westermo Eltec GmbH, Mainz.
All trademarks are the property of their owners. All rights reserved.

Revision: **2.0** | Date: **16.02.2024**